

 **Sealed Air**

FillTeck™

Inflatable Cushioning System



**The most versatile solution for
high-performance inflatable cushioning**

FillTeck™ Inflatable Packaging System

Customize the height and length of your cushion size with the touch of a button

Versatile and flexible Performance Cushioning



FillTeck™ inflatable cushioning systems provide custom performance cushioning for products of any shape and size. With the touch of a button, the operator has the ability to specify the height and length of the cushioning material. The versatility of FillTeck™ systems allows you to work on-line or batch material off-line.

FillTeck™ systems allow you to work on-line or batch material off-line.

Customize material height and length



A user-friendly control pad allows you to customize the height of FillTeck™ packaging from 12.5 mm to 100 mm, which reduces material usage and provides protection even in narrow spaces. Material is perforated or cut to a desired length, which

eliminates waste and creates superior cushioning around your entire product.

Create on-demand cushioning

FillTeck™ systems produce material on-demand, making them ideal for batching applications. Batched material rolls can be distributed to individual pack stations when and where they are needed. Material can also be used for packaging on a conveyor.

Choose the ideal material shape



The shape of FillTeck™ packaging can be changed at the touch of a button to provide maximum protection for your application. To wrap a product in FillTeck™ packaging, choose one of the quilted options which allow for the material to conform to irregularly shaped products. For bottom, top and side cushioning, create a protective pad by choosing an option with long cushions.



Unparalleled strength and performance

FillTeck™ systems utilize three different film types. FillTeck™ Standard is designed for light-duty cushioning applications. FillTeck™ Plus film provides additional strength for fragile items. FillTeck™ X film is for heavy products that require durable protection. A Sealed Air representative will help you select the right film for your application.



FillTeck™ X film – outstanding strength for heavy items

Superior bottom pad cushioning

FillTeck™ inflatable cushioning systems automatically produce cushioned pads in the length and height that you desire, enabling you to provide protection at the bottom of a carton. Guarding against shock, vibration and damage, the FillTeck™ inflatable cushioning systems ensures that your item arrives damage-free.

Specifications		
	FillTeck™ 400 System	Special Order FillTeck™ 600 System
Electrical:	220-240 V ~ Single Phase 8A 50/60 Hz	220-240 V ~ Single Phase 8A 50/60 Hz
Receptacle type	CE - IP55, 16A - 6h - 2P + ⊕, 200 - 250Volt	CE - IP55, 16A - 6h - 2P + ⊕, 200 - 250Volt
Pneumatic	1,8 KVA - 0,8 KW/h	1,8 KVA - 0,8 KW/h
Pressure minimum	6 bar	6 bar
Output minimum	240 Ltr/Min (FAD)*	240 Ltr/Min (FAD)*
Receiver minimum	75 Ltrs	75 Ltrs
Weight	380 kg	412 kg
Film width	420 mm	620 mm
Size (LWH)	980 mm x 1170 mm x 1440 mm	1170 mm x 1170 mm x 1440 mm

* (FAD) = Free Air Delivery



Protective Packaging
Telford Way, Kettering, Northants NN16 8UN, UK
Tel: +44 (0) 1536 315700 Fax: +44 (0) 1536 410576
E-mail: EPDeuromktg@sealedair.com
www.sealedair-emea.com

Our Products Protect Your Products®

Distributed by:

FT-GB-08-06

Corporate offices: Sealed Air Corporation,
200 Riverfront Boulevard, Elmwood Park, NJ 07407, USA
www.sealedair.com

Sealed Air has companies throughout the world.
© Sealed Air Corporation 2008. All rights reserved.

