

# EXS-158



36 STRAPS PER MINUTE



LOOP EJECTION



SIMPLE MACHINE HEAD WITH NO ANY CLUTCH



SECOND STRAP REFEED



ELECTRONIC OUTSIDE TENSION CONTROL



AUTO LAST STRAP EJECTION



▲ CONTROL PANEL



PATENT PENDING

## FEATURES

- HIGH SPEED 36 STRAPS/MIN
- ELECTRONIC OUTSIDE TENSION CONTROL
- NO PACKAGE NO TENSION
- EASY STRAP THREADING
- LOOP EJECTION
- 2<sup>nd</sup> STRAP REFEED
- AUTO LAST STRAP EJECTION
- SIMPLE MACHINE HEAD WITH NO ANY CLUTCH
- JOG SWITCH FOR SERVICE AND MAINTENANCE

## SPECIFICATION

- POWER SUPPLY: 100/110/220/230/240V, 50Hz/60Hz, 1-Phase
- POWER CONSUMPTION: 0.60kW
- SPEED: 36 STRAPS/MIN (SAME FOR 50/60Hz)
- STRAP WIDTH: 9, 12, 15MM,
- STRAP TENSION: 5-65 KG

### Arch Size

H/W (mm)	850	1050	1250	1450
600	S	V	V	V
800	V	V	V	V
1000	V	V	V	V
1200	V	V	V	V

