



minipack®
THE ORIGINAL PIONEER

MODULAR 50S

SEMI-AUTOMATIC PACKAGING MACHINE - L-SEALING - SEALING BAR 540X400 MM



DESCRIPTION

The **MODULAR LINE** semi-automatic, angular machines offer maximum packaging flexibility, and a quality product at a competitive price.

MODULAR 50S and **MODULAR 70**, which have recently been updated and revised, can be used to package products using any material, producing highly attractive results.

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151

MODULAR LINE uses an electronically controlled sealing system and the very latest safety devices. The lines can be used in automatic or semi-automatic mode, and the operating programs can be customised in order to simplify the packaging process and maximise productivity. The **INOX** version of **Modular 50** is perfect for food or pharmaceutical applications.

MODULAR 50S and **MODULAR 70** can also be used with the minipack-torre **TUNNEL LINE**.

TECHNICAL FEATURES

Electrical power supply	200V 50/60Hz 208/220V 60Hz 230V 50Hz 400V 50Hz 400V 50/60Hz 440V 50/60Hz
Phase	3Ph
MAX power installed	2,4 kW
Hourly output	0-900 p/h
Maximum current	12 A (200V) 11,5/10,9 A (208V/220V) 10,4 A (230V) 6 A (400V) 5,5 A (440V)
Available dimensions of the sealing bars	540x400 mm
MAX Reel Dimensions (diameter)	250 mm
MAX Reel Strip Dimensions (width)	600 mm
Work surface height	930 mm
Machine weight (Net/Gross)	151/182 kg
Machine dimensions sealing frame open	1565x750x h.1400 mm

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



minipack®
THE ORIGINAL PIONEER

Machine dimensions
sealing frame closed

1565x750x h.1100 mm

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL FEATURES

- Teflon coated sealing blade
- Double sealing bar with shock absorber
- Continuous cycle cooling system
- Manual or automatic mode
- Adjustable working plate
- Motor driven conveyor belt with adjustable speed
- Oversized waste film winder
- Integrated roll support
- Digital panel with 6 programs
- Product counter
- Lockable packaging plate
- Bar opening delay allows sealer to cool down
- Machine on wheels
- Emergency off switch.

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151